

Installation:



Surface Preparation

Surfaces must be dry and free of dirt, loose particles, oil, wax, grease or any other substance which may affect adhesion. The floor level must not vary beyond 3/16 of an inch per 10 feet. If some materials prove hard to remove during preparation, surface abrasion such as sand blasting or some similar method is required.

Application

Pour and trowel using the method of choice. Wear rubber gloves if skin contact may occur. Wipe any spill with a dry cloth, using mineral spirits if necessary. Clean the tools before the glue sets.

Trowel Recommendations

Trowel Dimensions	Floor Type	Coverage
3/16" x 1/4" x 1/2" V Notch 	3 ply, 5 ply and multi-ply engineered/laminated plank 6" wide or less and 5/8" thick or less. Solid flooring 3" wide or less and 1/2" thick or less.	~55 sq. ft. per gallon
1/4" x 1/4" x 1/4" Square Notch 	Solid flooring greater than 3" wide and 1/2" thick or less. 3/4" shorts and parquet.	~35 sq. ft. per gallon
1/8" x 1/8" x 1/8" Square Notch	Finger block parquet 1/2" thick or less.	~80 sq. ft. per gallon

Product Limitations and Application Directives

This adhesive is not a moisture barrier by itself. The adhesive must not be used on wet, frozen, friable or contaminated surfaces. Do not mix this adhesive, or add water to it in the pail.

Children can fall into bucket and drown. Keep children away from bucket with even a small amount of fluid.

Los niños corren peligro de caerse dentro del balde y ahogarse. Mantener a los niños lejos de los baldes, incluso cuando sólo tengan una pequeña cantidad de líquido.



Naturally Aged Flooring

Urethane Wood Flooring Adhesive

Description of Product

- Low V.O.C., one component, moisture curing polyurethane adhesive.
- Designed for easy trowel-on application over concrete or wood substrates to install materials such as: solid hardwood planks, laminated hardwood flooring and parquet flooring.

Performance Features and Benefits

- Low V.O.C. and low odor.
- Minimal shrinking, trowel ridge holding and non slump.
- Trowels easily, yet offers good wet / green grab.
- High bond strength.
- Cleans up easily prior to cure.

Physical Data

Color	Tan.
Tack Onset	Approximately 60 minutes at 70F and 45% relative humidity.
Cure Time	Under ambient conditions of around 70F and 45% relative humidity, the adhesive should set to allow light foot traffic after 4 hours. Normal traffic can resume after 12 hours. Higher humidity and temperature will accelerate set speed.
Shelf Life	Product is stable for 12 months in unopened container (store under ambient conditions in a dry area). Cured material is not considered hazardous.
Packaging	5 gallons of adhesive in a 5 gallon metal pail.

Warnings and Warranties

KEEP OUT OF REACH OF CHILDREN
PRODUCT INTENDED FOR INDUSTRIAL USE
STORE IN A TIGHTLY SEALED CONTAINER
AVOID DIRECT SKIN CONTACT
NOT FOR INTERNAL CONSUMPTION
CONSULT MATERIAL SAFETY DATA SHEET PRIOR TO USING THIS PRODUCT

Naturally Aged Flooring warrants this product to be in accordance with its' technical properties as outlined on its' data sheet for a period not exceeding 12 months following the date of installation, providing the Naturally Aged Flooring product has been stored in accordance with its' data sheet, used within the duration of its' shelf life and applied in full compliance with its' data sheet.

The user of this product determines its' suitability for any intended use and assumes all associated risks thereof. In the event of a warranty claim, Naturally Aged Flooring shall pay for reasonable material for a one time replacement of the area which is defective as a result of the adhesive as deemed by Naturally Aged Flooring. Sole remedy for buyer shall be limited to the replacement price of the aforementioned material exclusive of labor or cost of labor.

No warranty other than the aforementioned is expressed or implied regarding this product, including any warranty for the sale of this product for a particular application. Naturally Aged Flooring assumes no responsibility for personal injury or property damage to sellers, users or third parties caused by this material. Such sellers or users assume all risks associated with this material.

Safety Data

May contain calcium carbonate (CAS 1317-65-3),MDI/ methylenediphenylenediisocyanate(CAS 101-68-8).
Contains no California Proposition 65 listed chemicals.
Flash Point >200F. Volatile Organic Content (VOC) <100g/l

PRODUCT OF NATURALLY AGED FLOORING
805-520-4903